

Creep Resistant Refractory with Controlled Optical Emission

The United States Government has rights in this invention pursuant to contract no. DE-AC05-00OR22725 between the United States Department of Energy and UT-Battelle,
5 LLC.

The present invention relates to refractory materials and components capable of resisting creep deformation and chemical attack while radiating enhanced infrared energy over selected spectral regions.

10

Ceramic refractories are widely found in high-temperature, chemically demanding applications and are critical construction materials for energy-intensive industries. Refractories are made in many forms: the roof of a glass melting furnace is usually a self-supporting arch of dense alumina refractory bricks; ladles for molten steel or aluminum
15 may be lined with bricks or with a mixture that is rammed into place somewhat like concrete; high-temperature combustors can be lined with a lower density fibrous ceramic board or blanket, which may also serve as the host or support for a catalyst, often applied as a wash coat after the refractory is in place.

20 Refractory materials have remained largely unchanged for many years and fundamentally new refractory systems are needed because alumina-based materials are reaching their ultimate performance limits with respect to chemical and mechanical wear and tear. Areas where breakthroughs are needed are in strengthening the base refractory material for creep resistance, improving chemical resistance thereof, and, at the same time, giving it the
25 added functionality of acting as a host for advanced catalysts. For many boilers and furnaces, the time between rebuilds is directly related to the ability of the refractory to resist creep or sagging, corrosion, erosion, and other slow degradation processes.

The present invention described herein arose as an unexpected confluence of several
30 unrelated pieces of work concerning rare-earth doped alumina and similar materials. There is logical interest in oxide refractories for high-temperature applications in oxidizing environments where extremely creep-resistant materials such as carbides and nitrides are chemically unstable. Unfortunately, high-alumina ceramics exhibit high diffusion rates

that affect chemical stability, grain growth, and creep. At the same time, there is great interest in oxides or other refractories that have catalytic properties for catalytic combustors and other systems. Based on the analysis that follows, yttrium aluminum garnet, commonly known as "YAG", ($\text{Y}_3\text{Al}_5\text{O}_{12}$) holds promise to be a good refractory from creep and chemical resistance alone, and maybe an even more useful refractory if the emissivity can be tailored through doping.

Creep Resistance of YAG

- 10 Please see the following: T. A. Parthasarathy, T.-I. Mah, and K. Keller, "Creep Mechanism of Polycrystalline Yttrium Aluminum Garnet," *J. Am. Cer. Soc.* 75, 1756-1759 (1992); and T. A. Parthasarathy, T.-I. Mah, and L. Matson, "Deformation Behavior of an Al_2O_3 - $\text{Y}_3\text{Al}_5\text{O}_{12}$ Eutectic Composite in Comparison with Sapphire and YAG," *J. Am. Cer. Soc.* 76, 29-32 (1993). Those researchers reported high temperature deformation studies on bulk polycrystalline YAG compositions. Their testing method (displacement-controlled testing), which often introduces errors in the calculation and interpretation of strain, was used to generate stress-strain information. They found their YAG compositions and derivatives to be more creep resistant than alumina at all explored temperatures (1410, 1530, and 1650°C).
- 20 Others have tested single-crystal YAG or polycrystalline YAG fibers and also found them to be creep resistant. Please see: W. R. Blumenthal and D. S. Phillips, "High-Temperature Deformation of Single-Crystal Yttrium-Aluminum Garnet (YAG)," *J. Am. Cer. Soc.* 79, 1047-1052 (1996); S. S. Sternstein and R. Warren, "Dynamic and Transient Characterization of Ceramic Fibers at Elevated Temperatures," *Cer. Eng. Sci. Proc.* 18, 331-338 (1997); and G. N. Morscher, K. C. Chen, and K. S. Mazdiasni, "Creep-Resistance of Developmental Polycrystalline Yttrium-Aluminum Garnet Fibers," *Cer. Eng. Sci. Proc.* 18, 181-187 (1997)]. As will be discussed in greater detail, Applicants synthesized a large number of different materials and characterized their creep resistance using contact extensometry, which measures actual compressive strain of a specimen and thus eliminates errors in the calculation and interpretation of strain. It can be confidently stated that the compression test facilities and creep strain measurement capabilities used by Applicants are superior to those described by others who have tested YAG and

furthermore the data reported herein supports Applicants' claim that a general pattern of creep resistance exists for mixed-oxide materials having the garnet structure defined by the general formula $R_3Al_5O_{12}$ where R is at least one of Dy, Ho, Y, Er, Tm, Yb, and Lu. Also previously unrecognized is that all of these compounds are super-emissive and can serve as a host structure to a variety of dopants, thereby greatly expanding the available spectrum of radiant emitters while preserving key attributes of creep and chemical resistance and a common synthesis or processing route.

There apparently has not been any creep testing of other rare-earth garnets to determine if good creep resistance is in any way a general thing or is unique to YAG. The YAG materials tested by Parthasarathy et al. were arguably lacking creep resistance at 1530°C and above, so it is estimated that the threshold temperature for more severe-loading structural applications is likely to be $< 1500^\circ\text{C}$. However, for refractory applications, the applied loads are relatively small (compared to those of engine components, for example) and are often only due to the mass and thermal expansion of the superstructure itself. So service above 1500°C could be quite possible in such low-stress applications because the creep rates would be correspondingly small.

Chemical Resistance of YAG

YAG is an extremely stable oxide, as demonstrated by the following: R. J. Lauf and J. H. DeVan, "Evaluation of Ceramic Insulators for Lithium Electrochemical Reduction Cells," J. Electrochem. Soc. 139 [8], 2087-91 (1992). It was found to be one of very few insulating refractories to withstand contact with molten lithium. What was not appreciated therein is that resistance to chemical attack, especially to partial reduction, is a key attribute of the present invention, because Applicants intend to use the aluminum garnet phase as a host for optically active dopants in order to achieve the desired super-emissive behavior. It will be appreciated that if the host compound becomes partially reduced, the operative emission processes might shift or become quenched altogether. The most obvious effect of partial reduction is the creation of broad absorption bands in normally transparent oxides and this will interfere with optimal emission of fluorescent lines from the dopants or from the matrix itself in the case of compounds such as $Er_3Al_5O_{12}$.

Feasibility of YAG as an Emitter

Recent work by others has indicated that powders of rare-earth aluminum garnets were difficult to sinter. This is consistent with the expectation that YAG would be creep resistant, because similar microscopic processes govern creep and sintering kinetics. Interest in the rare-earth-doped garnets is not limited to structural applications but includes burners with controlled spectral emission for enhancing interaction with selected substrates for applications such as thermophotovoltaic (TPV) systems or paper drying. A TPV system burns gas in an incandescent mantle (like a camping lantern), and photovoltaic panels convert the light to electricity, thereby converting fuel to electricity with no moving parts. It should be noted that most TPV systems rely on a very low-density emitter, so creep strength is not a crucial attribute.

Prior work has tended to focus on thermal shock resistance and general fragility of the emissive materials rather than their creep strength *per se*. Others have been examining many different rare-earth doped materials to control the spectral emission from a burner specifically to better match the spectral response of silicon PV cells, to minimize IR heating and maximize conversion efficiency. Others have also attempted to improve the efficiency of gas-fired radiant burners for drying paper by altering spectral emission to better interact with water molecules. Various workers have shown that fluorescence lines of some rare-earth oxides may show up as distinctive features superimposed on the general blackbody emission. (All of these materials are broadly referred to as "super-emissive" in reference to their ability to emit larger amounts of light at certain wavelengths than would be expected based only on blackbody or gray-body emission.) If these wavelengths are selected to correspond to strong absorption bands in the gas phase, possibly large enhancements of reaction rates could occur. The significance of the effect and the effects of modifications, both in terms of dopants and in terms of structural substitutions, can only be determined experimentally.

A further body of work concerns thermophosphors used for non-contact temperature measurement. When these materials are excited by a pulsed laser (typically UV), the resulting optical emission at a longer wavelength decays with a time constant that is temperature dependent. Other workers have shown that doped YAG thermophosphors in

some cases can be used as high as 1400°C, suggesting that the operative electron energy states for fluorescence are not saturated at that temperature. See W. Lewis, W. D. Turley, H. M. Borella, and B. W. Noel, "Noncontact Thermometry in Excess of 2500 F using Thermographic Phosphors," in *Proceedings of the 36th International Instrumentation Symposium: Instrumentation for the Aerospace Industry* (Instrument Society of America, Research Triangle Park, North Carolina, 1990), pp. 23 – 27.

Based upon the foregoing, Applicants concluded that it was reasonable to formulate and test a number of different compounds to determine if they possess a unique combination of properties including: creep resistance; chemical or corrosion resistance; and optical emission over selected spectral regions. A further goal of this development program was to determine if these properties could be attributed to generalized groups of related compounds, or are unique to YAG.

A study of past developments revealed the following U.S. patents:

U.S. Patent No. 6,159,001 issued to Kushch, et al. on December 12, 2000 is typical of the general art of emissive bodies deployed in a burner to convert thermal energy to IR emissions. This patent describes "super-emissive materials" (typically rare-earth oxides) as coatings on a supporting structural refractory material (typically alumina but '001 also mentions glass, ceramic fibers, refractory metals, etc.)

U.S. Patent No. 6,126,888 issued to Goldstein on October 3, 2000 is a specific modification of the "relic method" in which a cloth structure is infiltrated with a metal precursor compound, which is then carefully burned to create a fibrous relic structure of the desired metal oxide. In '888 the item of claimed novelty is that the cloth is first carbonized before infiltration with the rare-earth precursor materials.

U.S. Patent No. 6,091,018 issued to Fraas, et al. on July 18, 2000 describes thermophotovoltaic systems employing a three-layer solid IR emitter. A structural support is provided by fiber-reinforced alumina. An intermediate black absorptive layer is provided to prevent shine-through for more spectral selectivity. The emissive layer is Ni- or Co-doped alumina, erbium oxide, or both.

U.S. Patent No. 5,942,047 issued to Fraas, et al on August 24, 1999 provides an excellent general description of TPV systems. It claims a multilayer emitter and discusses a “reinforcing layer” of SiC, silicon nitride, BN, and refractory metals. “Garnet” is mentioned as one choice for the emissive layer, but ‘047 does not specify what type of “garnet” is contemplated. In the absence of any defining information in the specification, one has to rely on the “textbook” definition of garnet as a family of naturally occurring cubic silicate minerals. None of these minerals is stable at elevated temperatures and atmospheric pressure, and therefore would not be suitable as a refractory. None of them could be prepared by sintering, since they are inherently high-pressure phases. The preferred emitter in ‘047 is MgO:Co and alumina:Co and it is noted that these have poor thermal shock performance. According to ‘047, “A variety of emitters are possible with the two important elements being continuous fiber reinforcement for durability and doping for spectral control.” Clearly, an inherently creep-resistant emitter is not contemplated nor taught by ‘047.

U.S. Patent No. 5,865,906 issued to Ferguson, et al. on February 2, 1999 describes another emitter based on Co-doped alumina or magnesia.

U.S. Patent No. 5,837,011 issued to Wong on November 17, 1998 is typical of many patents on making metal oxide fiber or cloth by the “relic method”, which has been known since the days of the Welsbach Mantle (pre-1900) [Carl Auer von Welsbach, Brit. Pat. No. 124]. The claimed materials in ‘011 are rare-earth oxides.

U.S. Patent No. 5,782,629 issued to Lannutti on July 21, 1998 describes a low-cost way to make a zirconia (ZrO_2) emitter using the *in situ* decomposition of zircon (ZrSiO_4). Zirconia is desired because of its superior mechanical properties compared to aluminosilicates.

U.S. Patent No. 5,686,368 issued to Wong on November 11, 1997 describes another “relic” method for making fibrous emitters. Several rare-earth oxides are claimed, along with the use of ThO_2 to control grain growth during sintering. ‘368 discusses the importance of fiber strength and flexibility but does not mention creep.

- U.S. Patent No. 5,601,661 issued to Milstein, et al. on February 11, 1997 describes certain specific types of narrow-band emitters (method of use patent). Described materials include Yb-Al garnet as well as Al_2O_3 and YbAlO_3 . Creep resistance is not cited as a performance attribute – the main objective in '661 is thermal shock resistance and all claims relate to fairly specific physical structures with well-defined pore distributions. The independent claim also includes “epoxies and plastics” in the list of candidate materials, which is clearly inconsistent with the intended use.
- 10 U.S. Patent No. 5,500,054 issued to Goldstein on March 19, 1996 describes a light pipe approach as a means of isolating the PV element from the thermal energy. Among the many claimed emissive materials are “aluminum-ytterbium-yttrium mixed oxides” but no mention is made of which phase or phases are desired and no mention is made of creep resistance, since the emitter material is not used in a structural role.
- 15 U.S. Patent No. 4,776,895 issued to Goldstein on October 11, 1988 describes an improved TPV system in which the emission wavelengths of the emitter are matched to the absorption band of the PV element.
- 20 The above study is not intended to be exhaustive. None of the cited references appear to suggest the inherent creep resistance of the specifically claimed family of compounds, nor the specific utility of a creep-resistant and chemical-resistant super-emitter, nor the fabrication of monolithic, strong super-emitters by liquid-phase sintering.
- 25 Therefore objects of the present invention include the provision of: a creep-resistant refractory material having super-emissive properties; a creep-resistant refractory material that is resistant to oxidation and chemical attack; a creep-resistant refractory material that is resistant to partial reduction in low-oxygen environments; and a family of similarly creep-resistant refractory materials having super-emissive properties over various selected spectral ranges, whereby their super-emission may be matched to the absorption bands of
- 30 a material or process to be heated.

Other objects of the present invention include the provision of methods of making: a creep-resistant refractory material having super-emissive properties; a creep-resistant refractory material that is resistant to oxidation and chemical attack; a creep-resistant refractory material that is resistant to partial reduction in low-oxygen environments; and a family of similarly creep-resistant refractory materials having super-emissive properties over various selected spectral ranges, whereby their super-emission may be matched to the absorption bands of a material or process to be heated.

Further objects of the present invention include the provision of methods of making a creep-resistant refractory material having super-emissive properties as a coating upon a lower-cost refractory material.

Other objects and advantages will be accomplished by the present invention, which is designed to create a highly stable, creep-resistant rare-earth aluminum garnet refractory characterized by super-emissivity over a desired spectral range. The spectral range may be defined by selectively doping with one or more rare-earth elements or transition metals and may be selected to enhance the radiative transfer of thermal energy to a selected chemical or industrial process. Some applicable purposes include combustion, pyrolysis, drying, selective chemical synthesis or decomposition, and others.

Further and other objects and advantages of the present invention will become apparent from the description contained herein, read together with the attached Drawings, which are briefly described as follows.

Fig. 1 illustrates creep strain versus time for a YAG refractory made in accordance with the present invention.

Fig. 2 illustrates the densification results for some rare-earth aluminum garnets of the present invention.

Fig. 3 illustrates the results of thermogravimetric analysis during processing of some of the compositions of the present invention.

Fig. 4 presents the densities of several of the compositions of the present invention after firing at 1800°C.

Fig. 5 presents the densities of several of the compositions of the present invention after firing at 1850°C.

Fig. 6 summarizes creep test data for YAG, ErAG, and DyAG made in accordance with the present invention.

Figs. 7a and 7b illustrate in an oblique view a layered refractory material made in accordance with another aspect of the present invention.

Figs. 8a and 8b illustrate in an oblique view an alternate layered refractory material made in accordance with another aspect of the present invention.

Figs. 9a and 9b are photomicrographs that illustrate, at lower and higher magnification, respectively, the microstructure of a YAG:Ce (1%) coating made in accordance with one aspect of the present invention.

Figs. 10a and 10b are photomicrographs that illustrate, at lower and higher magnification, respectively, the microstructure of a YAG:Sm (1%) coating made in accordance with one aspect of the present invention.

Based on the considerations enumerated above refractories have been made that are both creep resistant and have the ability to radiate selective spectral lines, usually in the IR spectrum (0.25 to 40 μm) controlled by the amount and type of dopants. It is known that not all rare-earth elements form the garnet phase ($\text{R}_3\text{Al}_2\text{O}_7$) with alumina. The most promising matrices would be Dy, Ho, Y, Er, Tm, Yb, and Lu aluminum garnets, since these elements have ionic radii, in the trivalent state, between 0.908 and 0.85 Å. Since the cost of rare-earth elements varies widely depending on their relative abundance, YAG, DyAG, and ErAG were examined as matrix phases.

In accordance with one aspect of the present invention, a creep-resistant and chemical-resistant ceramic refractory composition includes a mixed oxide of the general formula $R_3Al_5O_{12}$ where R is at least one of Dy, Ho, Y, Er, Tm, Yb, and Lu, the mixed oxide having a garnet structure and containing in solid solution at least one dopant of a transition metal element and/or a rare-earth element, which effects in the composition enhanced optical emission in at least one spectral range.

In accordance with another aspect of the present invention, a method of making a creep-resistant and chemical-resistant ceramic refractory composition includes the steps of:

- 10 Step a. mixing aluminum oxide and an oxide of at least one element R, where R is at least one of Dy, Ho, Y, Er, Tm, Yb, and Lu, in a molar ratio represented by the general formula $R_3Al_5O_{12}$;
- 15 Step b. adding at least one additional dopant element selected from transition metals and rare-earth elements, the dopant element selected to provide enhanced optical emission in at least one selected spectral range; and
- 20 Step c. heating the oxide mixture to a temperature of at least 1800°C to form by liquid-phase sintering a densified mixed oxide having a garnet structure and containing the dopant element in solid solution.

- 25 In accordance with a further aspect of the present invention, a super-emissive refractory article includes a refractory alumina-containing substrate having thereon a coating comprising rare-earth aluminum garnet formed by *in situ* reaction of a selected rare-earth oxide with the alumina, the garnet further including at least one optically active dopant of a transition metal element and/or a rare-earth element.

- 30 In accordance with yet another aspect of the present invention, a emissive refractory article includes a refractory alumina-containing substrate having thereon a coating comprising an emissive layer of a rare-earth oxide bonded to the substrate by an interlayer of rare-earth aluminum garnet formed by an *in situ* reaction between the rare-earth and the alumina.

In accordance with a further aspect of the present invention, a super-emissive ceramic refractory composition for use in reducing environments includes a garnet-structure mixed

oxide of the general formula $R_3Al_5O_{12}$ where R is at least one of Dy, Ho, Y, Er, Tm, Yb, and Lu, and containing in solid solution at least one additional dopant of a transition metal and/or a rare-earth element, which is selected to provide an enhanced optical emission in at least one selected spectral range, the refractory composition being resistant to reduction
5 and quenching of the optical emission by a reducing environment.

Skilled artisans will appreciate that while the large rare earth elements La, Nd, Sm, Eu, and Gd do not form the garnet phase with alumina, small amounts of these elements (probably less than about 10%) may be incorporated into the garnet structure. It will be
10 further appreciated that the levels of optical dopants (used for example in laser materials) is typically less than this amount. In the examples described herein, dopant concentrations were typically in the 1-5% range.

The narrative description and explanation below explains how some samples of novel
15 compositions were made in accordance with the present invention, and serves as an example of how small amounts of such compositions may be made. The exact amounts of materials used per se are not particularly critical to the invention.

Standard ceramic powder processing techniques were used to blend powder mixtures
20 containing the oxides in the proper proportion to yield the garnet phase $R_3Al_5O_{12}$, where R is yttrium (YAG), dysprosium (DyAG) or erbium (ErAG). Table 1 gives the properties of the starting materials used in the blends. Each of the rare-earth oxides was a minimum of 99% total rare-earth oxide (TREO).

25 (Table 1 begins next page.)

TABLE 1**Materials Used in the Synthesis of Rare-Earth Garnet Samples**

Oxide	Formula	Source	Lot #	Oxide/ TREO
Aluminum	Al ₂ O ₃	Baikowski CR-6	-	
"	"	Malakoff RC-HPT DBM	BM-2900	
"	"	Malakoff RC-LS DBM		
"	"	Malakoff RC-HPT DBM with MgO	2BL-2148	
		AKP-50	-	
Cerium	CeO ₂	Pacific Industrial Development Corporation (PIDC)	714802-0635	99.95%
Dysprosium	Dy ₂ O ₃	PIDC	816301-1830	99.9%
Erbium	Er ₂ O ₃	PIDC	917405-2230	99.9%
Gadolinium	Gd ₂ O ₃	PIDC	831001-1440	99.99%
Neodymium	Nd ₂ O ₃	PIDC	812401-1030	99.9%
Praseodymium	Pr ₆ O ₁₁	PIDC	906301-0825	99.5%
Samarium	Sm ₂ O ₃	PIDC	727404-123	99.9%
Terbium	Tb ₄ O ₇	PIDC	818702-1640	99.99%
Yttrium	Y ₂ O ₃	Molycorp		

5

Typically a 100 g batch of the doped powder was prepared by weighing the oxides into a 250 ml bottle along with typical amounts of polyvinylpyrrolidone (PVP) (average MW = 10,000) as a dispersant/binder and carbowax 8000 as a lubricant/binder. The powders were blended for about 5 hr in 100g of absolute ethyl alcohol at rolling mill with 300 g of alumina grinding media (6.45 mm OD x 6.35 mm length). After mixing, the oxide slurry was decanted from the media, and the media was washed 4 times with approximately 50 ml portions of alcohol.

- 15 The washes were combined with the slurry and the alcohol was evaporated at 55°C in an air-circulating drying oven. The large agglomerates in the dried powder were broken up by dry ball milling for about 2 hr with 10 mm yttria-doped zirconia balls. The resulting powder was sieved through a stainless steel No.100 U.S.A. standard testing sieve. The

oversize material was further reduced to pass through the No. 100 sieve by milling with a few zirconia media.

Table 2 gives the quantities used in the blends, and the calculated molar composition. The amount of media wear has been included in the total alumina added to the blends. The blends 78-1, 78-2 and 78-3 were used to make the creep test samples and were prepared in the same manner as the doped powders except that they were milled using 10 mm spherical yttria doped zirconia media (Performance Ceramics). Because of media wear, they contained a small amount of ZrO_2 .

(Table 2 begins next page.)

TABLE 2**Material Quantities Used in Powder Blends**

ID	Al ₂ O ₃ Source	Rare- earth	Dopant	Total Wt. in Mixture (g)					Molar Ratio of Elements			
				Re ₂ O ₃	Al ₂ O ₃	Dopant	PVP	carbowax 8000	Re	Al	Dopant	O
182-A	CR 6	Y ₂ O ₃	none	57.06	43.07		1.25	1.25	3.00	5.01	0.00	12.02
182-B	RC-HPT DBM	Y ₂ O ₃	none	57.06	43.09		1.25	1.25	3.00	5.02	0.00	12.03
182-C	RC-LS DBM	Y ₂ O ₃	none	57.06	43.26		1.25	1.25	3.00	5.04	0.00	12.06
182-D	RCHP DBM MgO	Y ₂ O ₃	none	57.06	43.10		1.25	1.25	3.00	5.02	0.00	12.03
182-E	AKP 50	Y ₂ O ₃	none	57.07	43.12		1.25	1.25	3.00	5.02	0.00	12.03
194-A	CR 6	Dy ₂ O ₃	none	68.70	32.11		1.24	1.25	3.00	5.13	0.00	12.19
194-B	RC-HPT DBM	Dy ₂ O ₃	none	68.70	32.13		1.25	1.25	3.00	5.13	0.00	12.20
194-C	RC-LS DBM	Dy ₂ O ₃	none	68.71	32.49		1.25	1.25	3.00	5.19	0.00	12.29
194-D	RCHP DBM MgO	Dy ₂ O ₃	none	68.70	32.09		1.25	1.25	3.00	5.13	0.00	12.19
194-E	AKP 50	Dy ₂ O ₃	none	68.70	32.21		1.26	1.25	3.00	5.15	0.00	12.22
222-A	CR 6	Er ₂ O ₃	none	69.24	30.67		1.24	1.25	3.00	4.98	0.00	11.98
222-B	RC-HPT DBM	Er ₂ O ₃	none	69.24	31.34		1.25	1.25	3.00	5.09	0.00	12.14
222-C	RC-LS DBM	Er ₂ O ₃	none	69.24	30.63		1.25	1.25	3.00	4.98	0.00	11.97
222-D	RCHP DBM MgO	Er ₂ O ₃	none	69.24	30.71		1.25	1.25	3.00	4.99	0.00	11.99
222-E	AKP 50	Er ₂ O ₃	none	69.24	30.61		1.25	1.25	3.00	4.98	0.00	11.96
276-A	RC-HPT DBM	Y ₂ O ₃	CeO ₂	56.34	42.90	0.88	1.24	1.25	2.97	5.01	0.03	12.03
276-B	RC-HPT DBM	Y ₂ O ₃	Gd ₂ O ₃	56.36	42.87	0.91	1.25	1.25	2.97	5.00	0.03	12.00

Total Wt. in Mixture (g)									Molar Ratio of Elements			
ID	Al ₂ O ₃ Source	Rare- earth	Dopant	Re ₂ O ₃	Al ₂ O ₃	Dopant	PVP	carbowax 8000	Re	Al	Dopant	O
276-C	RC-HPT DBM	Y ₂ O ₃	Pr ₆ O ₁₁	56.30	42.91	0.86	1.26	1.25	2.97	5.01	0.03	12.03
276-D	RC-HPT DBM	Y ₂ O ₃	Sm ₂ O ₃	56.32	42.90	0.88	1.25	1.25	2.97	5.01	0.03	12.01
21-A	RC-HPT DBM	Y ₂ O ₃	Er ₂ O ₃	56.25	42.79	0.96	1.24	1.25	2.97	5.00	0.03	12.00
21-B	RC-HPT DBM	Y ₂ O ₃	Tb ₄ O ₇	56.29	42.81	0.94	1.25	1.25	2.97	5.00	0.03	12.01
21-C	RC-HPT DBM	Y ₂ O ₃	Dy ₂ O ₃	56.28	42.80	0.94	1.26	1.25	2.97	5.00	0.03	11.99
21-D	RC-HPT DBM	Y ₂ O ₃	Dy ₂ O ₃	53.22	42.17	4.63	1.25	1.25	2.85	5.00	0.15	11.93
34-A	RC-HPT DBM	Y ₂ O ₃	Er ₂ O ₃	54.00	42.43	0.95	1.25	1.25	2.88	5.01	0.03	12.02
			Tb ₄ O ₇			0.93					0.03	
			Dy ₂ O ₃			0.93					0.03	
			Sm ₂ O ₃			0.87					0.03	
34-B	RC-HPT DBM	Dy ₂ O ₃	CeO ₂	68.07	31.36	0.63	1.25	1.25	2.97	5.01	0.03	12.02
34-C	RC-HPT DBM	Dy ₂ O ₃	Gd ₂ O ₃	68.03	31.35	0.67	1.26	1.25	2.97	5.01	0.03	12.01
34-D	RC-HPT DBM	Dy ₂ O ₃	Pr ₆ O ₁₁	68.07	31.36	0.63	1.25	1.25	2.97	5.01	0.03	12.02
43-A	RC-HPT DBM	Dy ₂ O ₃	Sm ₂ O ₃	68.04	31.32	0.64	1.25	1.25	2.97	5.00	0.03	12.00
43-B	RC-HPT DBM	Dy ₂ O ₃	Er ₂ O ₃	68.00	31.26	0.70	1.24	1.25	2.97	4.99	0.03	11.99
43-C	RC-HPT DBM	Dy ₂ O ₃	Tb ₄ O ₇	68.02	31.27	0.69	1.25	1.25	2.97	4.99	0.03	12.00
43-D	RC-HPT DBM	Dy ₂ O ₃	Nd ₂ O ₃	68.01	31.26	0.62	1.26	1.25	2.97	4.99	0.03	11.99

Total Wt. in Mixture (g)									Molar Ratio of Elements			
ID	Al ₂ O ₃ Source	Rare-earth	Dopant	Re ₂ O ₃	Al ₂ O ₃	Dopant	PVP	carbowax 8000	Re	Al	Dopant	O
51-A	RC-HPT DBM	Dy ₂ O ₃	Nd ₂ O ₃	65.27	31.28	3.10	1.24	1.25	2.85	5.00	0.15	12.00
51-B	RC-HPT DBM	Dy ₂ O ₃	Er ₂ O ₃	66.66	31.28	0.71	1.25	1.25	2.91	4.99	0.03	12.05
			Sm ₂ O ₃			0.64					0.03	
			Tb ₄ O ₇			0.69					0.03	
51-C	RC-HPT DBM	Er ₂ O ₃	CeO ₂	68.62	30.80	0.62	1.25	1.25	2.97	5.00	0.03	12.02
51-D	RC-HPT DBM	Er ₂ O ₃	Gd ₂ O ₃	68.57	30.79	0.66	1.26	1.25	2.97	5.00	0.03	12.00
92-A	RC-HPT DBM	Er ₂ O ₃	Pr ₆ O ₁₁	68.61	30.79	0.62	1.25	1.25	2.97	5.00	0.03	12.01
92-B	RC-HPT DBM	Er ₂ O ₃	Sm ₂ O ₃	68.59	30.78	0.63	1.25	1.25	2.97	5.00	0.03	12.00
92-C	RC-HPT DBM	Er ₂ O ₃	Dy ₂ O ₃	68.55	30.76	0.68	1.25	1.25	2.97	5.00	0.03	12.00
92-D	RC-HPT DBM	Er ₂ O ₃	Tb ₄ O ₇	68.57	30.77	0.68	1.25	1.25	2.97	5.00	0.03	12.01
139-A	RC-HPT DBM	Er ₂ O ₃	Dy ₂ O ₃	65.78	30.76	3.38	1.24	1.25	2.97	5.21	0.16	12.50
139-B	RC-HPT DBM	Er ₂ O ₃	Ce ₂ O ₃	68.83	30.89	0.28	1.26	1.25	2.97	5.00	0.03	12.00
139-C	RC-HPT DBM	Er ₂ O ₃	Dy ₂ O ₃	67.24	30.79	0.68	1.26	1.25	2.91	5.00	0.03	11.91
			Sm ₂ O ₃			0.64					0.03	
			Tb ₄ O ₇			0.69					0.03	
78-1	RC-HPT DBM	Y ₂ O ₃	ZrO ₂	142.65	107.35	0.35	3.13	3.13	3.00	5.00	0.01	12.01
78-2	RC-HPT DBM	Dy ₂ O ₃	ZrO ₂	171.75	78.25	0.50	3.13	3.13	3.00	5.00	0.03	12.03
78-3	RC-HPT DBM	Er ₂ O ₃	ZrO ₂	173.11	76.90	0.39	3.13	3.12	3.00	5.00	0.02	12.02

Cylindrical rods of sample materials 0.5 in. OD were prepared by uniaxial cold pressing the powders in a steel die using a standard laboratory press. A thin film of stearic acid was used as a release agent. As expected, the green density increased with an increase in the force used to compact the samples. The densification data for YAG is shown in Fig. 2.

- 5 Ten to fifteen grams of powder were pressed at 35 MPa. and the cold pressed rods were further compacted in an isostatic press at 345 MPa. Isostatic pressing was done with the samples sealed inside an evacuated latex rubber bag to prevent contamination from the compression fluid. The final green densities were the highest for the YAG compositions, and were the lowest for the ErAG composition. The densities were lower for the powders
10 blended with CR-6 alumina, and were the highest for the blends using RC-LS DBM alumina.

- The organic binders were removed from the green samples by heating in air. Thermogravimetric analysis and differential thermal analysis of pressed pellets of the
15 undoped blends showed that the samples began losing weight rapidly around 200°C. As shown in Fig. 3, associated with this weight loss was an exotherm that reached a maximum around 335°C. Furthermore, by the time the sample temperature had reached 600°C, greater than 90% of the weight loss had occurred. Based on this decomposition behavior, the binder was removed by heating to 300°C at 1°C/min; holding at 300°C for 1
20 hr.; heating at 1°C/min to 600°C and holding for 1 hr before cooling to room temperature.

- Several different grades of alumina are commercially available. Impurities, as well as the particle size of the starting powders, can affect (1) the rate of densification, (2) the sintered density and (3) the high temperature creep rate of the final ceramic. Initially YAG, DyAG
25 and ErAG were blended using the commercial alumina powders shown in Table 1. The blends were wet milled and the average particle sizes were determined using a laser particle size distribution analyzer.

- The effects that the alumina grade, the anneal time and the anneal temperature have on the
30 density of the product was investigated by heating isostatically pressed disks in a tungsten vacuum furnace under a vacuum of $\sim 2 \times 10^{-5}$ torr. The densities (expressed as % theoretical density(TD)) of the samples sintered for 5 hr at 1800 and 1850°C are shown in Figs. 4 and 5, respectively. All samples tested sintered to at least 85% TD, and some

samples sintered to about 98% TD. At both temperatures, the YAG sintered to the highest density and the DAG had the lowest density. For most of the compositions, the samples heated at 1800°C had a higher density than the samples heated at 1850°C. The type of alumina used in the blend had a pronounced effect on the final densities for the DAG and ErAG composition. Powder blended with RC-LS DBM and with AKP-50 grades gave the highest densities. The RC-HP DBM with added MgO (519 ppm) usually resulted in the lowest density. The grade of alumina had little effect on the YAG densities. The RC-LS DBM alumina had the largest amount of impurities of the aluminas used in the blends. The major impurities were Fe₂O₃ (146 ppm), Na₂O (548 ppm), SiO₂ (404 ppm), CaO (414 ppm), MgO (9 ppm) and ZnO (87 ppm). Because of the concern that impurities may increase the creep rate due to glass formation during sintering, the doped specimens and the creep specimens were formulated using the higher purity RC-HPT DBM alumina. This alumina contains Fe₂O₃ (53 ppm), Na₂O (79 ppm), SiO₂ (37 ppm), CaO (79 ppm) and MgO (19 ppm).

EXAMPLE I

Creep testing was carried out as described by A. A. Wereszczak, M. K. Ferber, T. P. Kirkland, A. S. Barnes, E. L. Frome, and M. N. Menon, "Asymmetric Tensile and Compressive Creep Deformation of Hot-isostatically-pressed Y₂O₃-Doped-Si₃N₄," *J. Eur. Cer. Soc.* 19, 227-237 (1999). The preliminary data generated at 1200°C indicated that the creep deformation in the rare-earth garnets was negligible. Therefore, the results described below focus on the 1300°C data. A typical creep strain versus time curve generated for the YAG specimen is shown in Fig. 1. To compare the creep response of the various materials, the minimum creep rate was calculated for each stress segment. Fig. 6 summarizes these data. The creep performance of all 3 rare-earth aluminum garnets exhibited was significantly better than that of the AD995 alumina. Furthermore, the creep curve for YAG material was approximately 100 times better than the alumina curve. The slopes of the creep rate versus stress curves were comparable for all materials (approximately 1) with the exception of the ErAG which exhibited a negative stress dependency. For this material, it is likely that the other time dependent processes affecting specimen length (phase transformations, sintering, etc.) occurred in addition to the creep.

The creep data presented in Fig. 6 are particularly striking in view of the fact that that none of the samples were fully dense. The skilled artisan will appreciate the engineering implications thereof. Material that is less than fully dense will have better insulating properties, which are contemplated to be important for many refractory applications. Moreover, if these materials were made into a fully dense condition (by longer sintering or more reactive starting powders, for example) they would be even more creep resistant, which is also contemplated to be important for many refractory applications. Thus, such properties are easily controllable and preselectable.

10

EXAMPLE II

15

20

To demonstrate that rare-earth fluorescence was possible from the samples, each sample was illuminated with UV light ($\lambda \sim 0.38 \mu\text{m}$) and checked for visible fluorescence. About half of the doped samples exhibited visible fluorescence. For example, bright yellow fluorescence was observed from the YAG:Ce(1%) sample. Regions of non-fluorescence were present in the samples that did fluoresce, indicating that the sample was not completely single phase and/or the dopant species was not uniformly distributed. Visible fluorescence of doped YAGs is summarized qualitatively in Table 3. All of the doped ErAG appeared to have a fluorescent dull violet color and all of the doped DyAG appeared dull brownish green.

(Table 3 begins next page.)

25

TABLE 3**Visible fluorescence of doped YAGs**

Dopant	Color	Intensity
1% Ce	yellow	bright
1% Gd	brown	dull
1% Pr	brown	dull
1% Sm	orange	bright
1% Er	yellow-green	medium
1% Tb	yellow-lemon	dull
1% Dy	peach	medium
5% Dy	peach	not noted

EXAMPLE III

10 Selected samples were also illuminated with a UV lamp while observing them in an IR camera and it was seen that IR emissions increased while under illumination, thereby further demonstrating that the materials were super-emissive in the IR spectral region.

15 In view of the foregoing results, various experiments were conducted to develop suitable processing schemes for both monolithic materials and coatings based on the claimed compositions.

EXAMPLE IV

20 Consideration of the $\text{Al}_2\text{O}_3\text{-Y}_2\text{O}_3$ phase diagram indicated that eutectics existed on either side of the desired $\text{Y}_3\text{Al}_5\text{O}_{12}$ compound. When an intimate mixture of the pure oxides was heated to a temperature just above this eutectic point, liquid phases were formed, which rapidly infiltrated throughout the structure, giving fairly rapid

25 densification. Once the entire sample had been converted to the garnet structure,

sintering ceased and the material was highly refractory and creep resistant, even if less than fully dense.

5 The transient liquid phase appeared to be a general property of the compositions of the present invention and has further implications for making coatings by *in situ* reactions with an alumina-containing substrate, as will be described in the following examples.

EXAMPLE V

10 Based upon the foregoing considerations, a layered refractory material is made wherein specific rare-earth elements and dopants are applied to the radiant surface of a lower-cost alumina refractory substrate. As shown in Fig. 7a, a relatively thin R_2O_3 layer 10 is applied to the surface of the alumina substrate 11. (R = at least one rare earth element, for example, Y) During firing these materials react to form a layer 12 that is substantially $R_3Al_5O_{12}$. Any desired dopants are incorporated into the coating at the same time by mixing their constituent oxides with the R_2O_3 . Some alumina is optionally added to the coating 10 to further improve the reactive bonding process.

EXAMPLE VI

20 A further modification of the compositions of the present invention is shown in Fig. 8. In this example, a thicker R_2O_3 layer 20 is applied to an alumina refractory 11'. After the *in situ* reaction is complete, some unreacted rare-earth oxide 23 exists at the surface, bonded to the substrate 11' by an intermediate $Y_3Al_5O_{12}$ layer 12'.

EXAMPLE VII

25 Paints comprising about 30 vol. % doped YAG precursor powder, 47 vol. % water and 23 vol. % glycol ether were formulated according to Table 4 as follows: Into a 30 ml bottle was placed a weighed amount of the mixed oxide powder and about 6 g of 1 mm spherical ZrO_2 grinding media. Deionized water (2 ml) and propylene glycol methyl ether (PGME) (1 ml) were added with a syringe. The mixture was

sonicated in an ultrasonic bath for 30 minutes to produce a suspension. Because the suspension settled with time, the paints were mixed by shaking prior to each use.

The paints were brushed onto an Alumina/Zirconia board, dried at room temperature and then heated to 1600 °C at 10 °C/min in an air circulating furnace with a 1 hr dwell time at 1600 °C. After firing, these coatings displayed characteristic fluorescence when illuminated by UV light. The coatings were thin, dense, scratch resistant, and adhered strongly to the substrate.

The fired coatings were examined by scanning electron microscopy (SEM) at magnifications ranging from 1000 to 10,000x. Figs. 9a and 9b illustrate, at lower and higher magnification, respectively, the structure of a YAG:Ce (1%) coating. Several surprising features can be seen in the photomicrograph. First, the coating is very highly sintered, as shown by the rounded polygonal grain structure. More surprisingly, there are well-distributed openings in the film, thereby forming a reticulated structure. This reticulated structure further enhances the emissivity, so the end result is a mantle-like emissive structure, but one that is simultaneously strong and securely attached to the underlying substrate. This combination of properties was unexpected for these compositions.

Figs. 10a and 10b illustrate the structure of a YAG:Sm (1%) coating at the same respective magnifications as the previous figure. Several surprising features become evident. First, the overall structure is well sintered, yet the individual grains in the coating are finer by about a factor of five, even though the only difference between the two samples is the particular rare earth dopant used. Second, this coating unexpectedly also contains distributed porosity that contributes to improved emissivity even though the coating is strong and adherent to the substrate.

The structure of the YAG:Pr coating was found to have a structure similar to that of the YAG:Ce coating. The structure of the YAG:Tb coating was found to have a structure similar to that of the YAG:Sm coating.

TABLE 4**Composition of doped YAG paints**

YAG	Dopant	1 mm ZrO ₂ media (g)	Powder (g)	Water (g)	PGME (g)
12-A	1% Ce	6.085	5.605	1.992	0.915
12-B	1% Tb	6.148	5.461	1.988	0.927
12-C	1% Sm	6.217	5.662	2.001	0.922
12-D	1 % Pr	6.393	5.525	2.013	0.932

5

It will be appreciated that it might be desirable to introduce more than one dopant element into a given system, thereby taking advantage of several sets of emission lines simultaneously. At the same time, placing several dopants into one host crystal can introduce unexpected energy states that can have the effect of quenching out previously active emission lines. To avoid this problem, the coating technique described in the previous example can be further modified as follows.

10

EXAMPLE VIII

15

An undoped layer of R₂O₃ is first disposed upon the substrate. Then, several dopants are applied to different areas of the surface (analogous to pixels on a color television screen) so that each "pixel" is free to radiate its characteristic spectral lines without unwanted absorption effects from the other dopants. After firing, the surface will then have the property of being able to radiate many different spectral lines into the surrounding gas phase.

20

It has thus been shown that extremely high creep resistance can be achieved in various rare-earth aluminum garnets while also allowing the selection of a large number of optically active dopants. Furthermore, by forming the garnet compound during sintering (by starting with the constituents as pure oxides) one can easily densify the material and assure that the dopants become effectively incorporated into the host garnet phase. By

25

contrast, YAG powder, once synthesized, is very poorly sinterable. Applicants have discovered, surprisingly, that while YAG is perhaps the best matrix from the standpoint of creep resistance alone, other rare-earth aluminum garnets have creep resistance that is still 10 times better than that of alumina. It is contemplated that the superior creep resistance of YAG can now be reliably extended to other rare-earth aluminum garnets and that these same garnets can serve as extremely stable hosts to many dopants, thereby creating more opportunities for selective emission. These alternative matrices provide more possibilities for hosting dopants with spectral emissions in selected regions for selected applications.

10 While it is contemplated that monolithic refractories are most useful where high-temperature strength is desirable, the compositions of the present invention are also suitable for wash coats in some applications. It is particularly important to note that the cost of the rare-earth elements can be minimized by making a "generic" YAG material and merely doping the outer surface with a selected dopant (many of which are much more costly than Y). It is also possible to apply a Y_2O_3 coating (containing small amounts of other rare-earth dopants) to an alumina refractory and fire it to form the garnet phase *in situ* over a base layer of less costly alumina as described in the foregoing examples.

15 Skilled artisans will appreciate that several factors must be considered in selecting the exact coating composition and thickness for a particular application. First, for cases where high rates of wear or erosion might be expected and the cost of downtime is high, a thicker coating (several millimeters) might be desired. Conversely, for the case of very costly dopants and low wear rates, a thinner coating (perhaps 50 microns) might be more desirable. It will also be appreciated that the optical emission from the coating will generally originate near the surface, so an excessively thick coating would not make optimal use of the active species.

20 It will be appreciated that the compositions of the present invention allow the designer to exploit the favorable creep properties of rare-earth aluminum garnets and the super-emissive properties of rare-earth oxides in general. Moreover, the outstanding resistance of YAG to reducing environments further enhances its utility as a stable host for optically active dopants.

- It will be understood that the compositions of the present invention can also be formed by other techniques similar in principle to the methods described in the foregoing examples. For example, all of the aforescribed oxides may be synthesized as very fine, highly reactive powders by sol-gel, alkoxide, coprecipitation, or similar processes. The materials
- 5 can also be made in low-density form by fiber extrusion or by well-known relic methods if an extremely creep-resistant emissive mantle is needed for demanding applications. Thus, using the teachings contained herein, the skilled artisan can achieve the optimal combination of properties for a given application without undue experimentation.
- 10 While there has been shown and described what are at present considered the preferred embodiments of the invention, it will be obvious to those skilled in the art that various changes and modifications can be prepared therein without departing from the scope of the inventions defined by the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
220